

STANDARD ACCESSORIES

BULL-LINE PULL TAPE WOVEN LOCATABLE

- ▶ Incorporates a tracer wire for signal locating
- ▶ Corrosion resistant fibers and conductor
- ▶ 22 AWG conductor - orange nylon jacketed
- ▶ Wire conductors can be easily spliced in the field
- ▶ High performance Stiff-Tape™ lubricated coating
- ▶ Best burn-through (conduit cutting) resistance
- ▶ Excellent blowability into conduit
- ▶ Accurate sequential foot or meter markings every 2 feet
- ▶ Can be pre-installed into conduit
- ▶ Exceeds requirements of Bellcore GR-356-CORE
- ▶ Available on reels in a wide variety of lengths



<p>TENSILE STRENGTH RANGE 500lb – 2,500lb (227kg – 1,136kg)</p>
<p>APPROXIMATE WIDTH 1/4" – 3/4" (6mm – 19mm)</p>

STOCKING INFORMATION WOVEN LOCATABLE PULL TAPE



DESCRIPTION	LENGTH	REEL SIZE	TYPE	PART #
WP05LC tensile: 500lb width: 1/4" (6mm) weight/ft: 0.00564lb	5000'	12"	P	20000323
WP10LC tensile: 1,000lb width: 7/16" (11mm) weight/ft: 0.00903	3,000'	13"	P	20002194
WP12LC tensile: 1,250lb width: 1/2" (13mm) weight/ft: 0.0103lb	1000'	8"	W	20000140
	3000'	13"	P	20000059
	5000'	14"	P	20000061
	10000'	18"	P	20000058
WP18LC tensile: 1,800lb width: 5/8" (16mm) weight/ft: 0.0131lb	500'	8"	W	20000225
	1000'	12"	P	20000221
	3000'	14"	P	20000163
	5000'	16"	P	20000313
	5500'	16"	P	20000384
	10000'	18"	P	20002187
	available in meters	900m	14"	P
	1000m	16"	P	20003874
	1800m	16"	P	20003890
	2000m	16"	P	20002191
WP25LC tensile: 2,500lb width: 3/4" (19mm) weight/ft: 0.0168lb	1000'	12"	P	20000279
	3000'	16"	P	20000155
	5000'	16"	P	20000174
available in meters	900m	16"	P	20003588
	2000m	22"	P	20003862

W=Wood P=Plastic WB=Wood Boxed
all tape widths are approximate



An Orbia Connectivity Solutions business.

+1 800 847 7661
WWW.DURALINE.COM



STANDARD ACCESSORIES

BULL-LINE PULL TAPE SHIPPING INFORMATION



polyester



locatable



aramid



SHIPPING INFORMATION ALL TAPE STYLES

REEL SIZE	REEL WEIGHT (LBS)	REELS/PALLET	PALLET SIZE
8" Wooden	1.5	100	45" x 45"
12" Plastic	2.2	48	45" x 45"
13" Plastic	2.3	36	45" x 45"
14" Plastic	3.5	36	45" x 45"
14" Wooden	4.5	36	45" x 45"
14" Wooden Boxed	4.5	36	45" x 45"
16" Plastic	4.4	18	45" x 45"
18" Plastic	5.0	10	45" x 45"
18" Wooden	7.8	10	45" x 45"
18" Wooden Boxed	7.8	8	45" x 45"
22" Plastic	7.4	8	45" x 45"
24" Wooden	14.0	4	45" x 45"



An Orbia Connectivity Solutions business.

+1 800 847 7661
WWW.DURALINE.COM



BULL-KNOT JOINING PROCEDURE

The following joining procedures for Bull-Line® Pull Tape were developed for tying two lengths of Bull-Line™ together or tying one length of Bull-Line® to a pulling swivel or pulling eye. The Bull-Knot was developed to be simple to tie yet provide consistent high strength. It is compact in size which minimizes hangup when pulling through the conduit system. In laboratory tensile testing and actual field use, the Bull-Knot has proven to be more reliable and outperforms "bowline" and other more recently developed pull tape knots. The Bull-Knot also works well on lubricated Bull-Line®.

JOINING TWO LENGTHS OF BULL-LINE®



STEP 1: Double up 12 inches of Bull-Line®.



STEP 2: Tie a loose overhand knot.



STEP 3: Retrace the original overhand knot with a double strand of the adjoining tape end.



STEP 4: Keep the flat surface in continuous contact between the two tape lengths.



STEP 5: Pull slack out evenly from both ends.



STEP 6: Wrap completed Bull-Knot ends with vinyl tape.

JOINING ONE LENGTH OF BULL-LINE®



STEP 1: Double up 24 inches of Bull-Line® end to be joined to the swivel or pulling eye.



STEP 2: Tie a loose overhand knot in the double strand, about 18 inches away from the free tape end.



STEP 3: Thread the free end through the pulling eye or swivel.



STEP 4: Retrace the original overhand knot with the double stranded free end.



STEP 5: Keep the flat surface in continuous contact between the two doubled tape lengths. Pull slack out evenly from both ends and wrap completed Bull-Knot ends with vinyl tape.

