

STANDARD ACCESSORIES

# SHUR-LOCK II COUPLER

- ▶ Designed for coupling HDPE & PVC conduit
- ▶ Can also be used to couple dissimilar conduits such as HDPE to PVC, threaded or non-threaded metal conduit, or fiberglass (FRP) conduit
- ▶ Stainless steel band clamps (hand tightened using a 5/16" nut driver) and locking ring
- ▶ Pre-lubricated O-ring forms an air-tight seal to withstand 125 PSI
- ▶ One person installation; re-enterable, no special tools required
- ▶ Air- and water-tight
- ▶ No ID reduction
- ▶ Excellent pull-out strength on HDPE, PVC, FRP and steel
- ▶ No-Stop version available for confined areas or repairs (\*NS)
- ▶ Specialized for use by electrical installers requiring ETL/UL listing
- ▶ Listed to UL STD 514B and ETL Listed to CSA STD C22.2 18.3-04
- ▶ NOTE: Certain sizes ETL-listed for use with HDPE and PVC for underground and concrete encased applications only! Not for use with PVC in above-ground applications. Not premise (indoor) rated
- ▶ UV resistant



ORDER REFERENCE

DESCRIPTION		NOMINAL PULL-OUT STRENGTH (LBS)	PACKAGING	SHIP WEIGHT (LBS)/CTN	PART #
1" Shur-Lock II Coupler SDR 1.315" ± 0.020"		600	10/ctn	4.5	20000118
1 1/4" Shur-Lock II Coupler SDR 1.660" ± 0.020"		700	10/ctn	5.2	20000120
1 1/4" Shur-Lock II Coupler HYB 1.590" ± 0.020"		700	10/ctn	5.2	20000121
1 1/2" Shur-Lock II Coupler SDR 1.900" ± 0.020"		700	10/ctn	5.8	20000122
2" Shur-Lock II Coupler SDR 2.375" ± 0.020"		700	10/ctn	6.7	20000123
2" Shur-Lock II Coupler-Extended SDR 2.375" ± 0.020" (8.25" long vs 5.75" standard)		700	10/ctn	6.7	20000264
2 1/2" Shur-Lock II Coupler SDR 2.875" ± 0.020"		1,000	6/ctn	7.7	20000172
3" Shur-Lock II Coupler SDR 3.500" ± 0.020"		1,000	6/ctn	9.8	20000173
4" Shur-Lock II Coupler SDR 4.500" ± 0.020"		1,000	4/ctn	10.7	20000245
5" Shur-Lock II Coupler SDR 5.563" ± 0.020"		1,000	2/ctn	8.3	20000254
6" Shur-Lock II Coupler SDR 6.625" ± 0.020"		1,000	2/ctn	9.9	20000256

 Please specify if ETL listing is required



An Orbia Connectivity Solutions business.

+1 800 847 7661  
WWW.DURALINE.COM



## SHUR-LOCK II COUPLER W/NO CENTER STOP

Center stop is removed to allow the coupler to be pulled back over the end of the duct for limited clearance installations.

DESCRIPTION		NOMINAL PULL-OUT STRENGTH (LBS)	PACKAGING	SHIP WEIGHT (LBS)/CTN	PART #
1" Shur-Lock II Coupler SDR 1.315" ± 0.020"		600	10/ctn	4.5	20002340
1 1/4" Shur-Lock II Coupler SDR 1.660" ± 0.020"		700	10/ctn	5.1	20000236
1 1/2" Shur-Lock II Coupler SDR 1.900" ± 0.020"		700	10/ctn	5.7	20002341
2" Shur-Lock II Coupler SDR 2.375" ± 0.020"		700	10/ctn	6.7	20000237
2 1/2" Shur-Lock II Coupler SDR 2.875" ± 0.020"		1,000	6/ctn	7.6	20000238
3" Shur-Lock II Coupler SDR 3.500" ± 0.020"		1,000	6/ctn	9.7	20000239
4" Shur-Lock II Coupler SDR 4.500" ± 0.020"		1,000	4/ctn	10.6	20000260
5" Shur-Lock II Coupler SDR 5.563" ± 0.020"		1,000	2/ctn	8.1	20001531
6" Shur-Lock II Coupler SDR 6.625" ± 0.020"		1,000	2/ctn	9.6	20000261

## RECOMMENDED ACCESSORY: SHUR-LOCK SPREADER TOOL

Used to spread the tabs of large OD Shur-Locks for easier installation.

DESCRIPTION	PACKAGING	PART #
3" Shur-Lock Spreader Tool	each	20095364
4" Shur-Lock Spreader Tool	each	20095365
6" Shur-Lock Spreader Tool	each	20095366

